



## DECLARATION OF PERFORMANCE (According to Regulation EU 305/2011, Annex V)

No: 001DOP-NG

- Identification code of the product type: Dry Pressed Ceramic Tiles, Group BIII E<sub>b</sub> >%10 Annex L
   (GL)
- 2. Type batch or serial number or any other element allowing identification of the construction product: Identification code of the product type, barcode number, ship date
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: For internal walls
- 4. Name,registered trade name or registered trade mark and contact address of the manufacturer:

NG Kütahya Seramik Porselen Turizm A.Ş. NG Kütahya Seramik

Trade Mark: NG KÜTAHYA SERAMİK

Atatürk Bulvarı Çalca Mah. Kütahya/ TURKEY

- Name and contact address of the authorized representative : Not relevant.
- 6. System or system of assesment and verification of constancy of performance of the construction product: System 4
- 7. Declaration of performances concerning a construction product covered by a harmonised standard: NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.
- 8. Declaration of performances concerning a construction product for which a European Technical Assesment has been issued: Not relevant.

9. Declared performances:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1	EN 14411:2016
Breaking strenght	Thickness ≥ 7,5 mm >600N Thickness <7,5mm >200 N	EN14411:2016
Release of dangerous substance,	for:	
- Cadmium	NPD	EN 14411:2016
- Lead	NPD	EN 14411:2016
Bond strength/adhesion, for:		
- Cementitious adhesives, Type C1	≥ 0,5 N/mm <sup>2</sup>	EN 14411:2016
- Reaction resin adhesives	NPD	EN 14411:2016
- Dispersion adhesives	NPD	EN 14411:2016
Durability for:		
- Internal use:	Pass	EN 14411:2016

**10.Declaration:** The performance of the product identified in point 1 is in conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ali ABACI / General Manager Kütahya/TURKEY- 11.06.2019 PORSELEN TURIZM A.Ş.
Atatürk Bulvarı Çalca Mary KÜTAHYA
T: 0 274 225 12 00 F: 144 225 12 13





## DECLARATION OF PERFORMANCE (According to Regulation EU 305/2011, Annex V)

No: 002DOP-NG

- Identification code of the product type: Dry Pressed Ceramic Tiles With Low Water Absorption, Group Bla E<sub>b</sub> ≤%0,5 Annex G, (GL/UGL)
- 2. Type batch or serial number or any other element allowing identification of the construction product: Identification code of the product type, barcode number, ship date
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Internal or external floor or wall coverings.
- 4. Name,registered trade name or registered trade mark and contact address of the manufacturer: NG Kütahya Seramik Porselen Turizm A.Ş. NG Kütahya Seramik Trade Mark: NG KÜTAHYA SERAMİK Atatürk Bulvarı Çalca Mah. Kütahya/ TURKEY
- 5. Name and contact address of the authorized representative: Not relevant.
- System or system of assesment and verification of constancy of performance of the construction product: System 4
- 7. Declaration of performances concerning a construction product covered by a harmonised Standard: NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.
- 8. Declaration of performances concerning a construction product for which a European Technical Assesment has been issued: Not relevant.

9. Declared performances:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1 <sub>FL</sub> /A1	EN 14411:2016
Breaking strength	Thickness ≥7,5mm >1300 N Thickness <7,5mm >700 N	EN 14411:2016
Slipperiness (1)	Refer to the technical documentation or catalog	EN 14411:2016
Release of dangerous substance, for	:	
- Cadmium	NPD	EN 14411:2016
- Lead	NPD	EN 14411:2016
Resistance to thermal shock	Pass	EN 14411:2016
Tactility	NPD	EN 14411:2016
Bond strength/adhesion, for:		
- Cementitious adhesives, Type C2	≥ 1,0 N/mm <sup>2</sup>	EN 14411:2016
- Reaction resin adhesives	NPD	EN 14411:2016
- Dispersion adhesives	NPD	EN 14411:2016
Durability for:		
- Internal use:	Pass	EN 14411:2016
- External use: freeze-thaw resistance	Pass	EN 14411:2016

Note: (1) where required by regulations

**10.Declaration:** The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: Ali ABACI / General Manager Kütahya/TURKEY- 05.10.2018 NG KÜTAHYA SERAMIK PORSELEN TURİZLI A.Ş. Atatürk Bul. Çalca Yahl KÜT (1984) Tel: 0.274.225 12 00 Haks: 226 1 1 3 Çinili V.D. 607 027 3850 Mersis No. 0607-0273-8560-0015





## DECLARATION OF PERFORMANCE (According to Regulation EU 305/2011, Annex V)

No: 003DOP-NG

- Identification code of the product type: Dry Pressed Ceramic Tiles With Low Water Absorption, Grup Bl<sub>b</sub> %0,5 < Eb ≤ %3 Annex H, (GL)</li>
- 2. Type batch or serial number or any other element allowing identification of the construction product: Identification code of the product type, barcode number, ship date
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Internal floor or wall coverings.
- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

NG Kütahya Seramik Porselen Turizm A.Ş. NG Kütahya Seramik Trade Mark: NG KÜTAHYA SERAMİK Atatürk Bulvarı Çalca Mah. Kütahya/ TURKEY

- 5. Name and contact address of the authorized representative: Not relevant.
- 6. System or system of assesment and verification of constancy of performance of the construction product: System 4
- 7. Declaration of performances concerning a construction product covered by a harmonised Standard: NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.
- 8. Declaration of performances concerning a construction product for which a European Technical Assesment has been issued: Not relevant.

9. Declared performances:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1 <sub>FL</sub> /A1	EN 14411:2016
Breaking strength	Thickness ≥7,5mm >1100 N Thickness <7,5mm >700 N	EN 14411:2016
Slipperiness (1)	Refer to the technical documentation or catalog	EN 14411:2016
Release of dangerous substance, fo	r:	
- Cadmium	NPD	EN 14411:2016
- Lead	NPD	EN 14411:2016
Tactility	NPD	EN 14411:2016
Bond strength/adhesion, for:		
- Cementitious adhesives, Type C2	≥ 1,0 N/mm <sup>2</sup>	EN 14411:2016
- Reaction resin adhesives	NPD	EN 14411:2016
- Dispersion adhesives	NPD	EN 14411:2016
Durability for:		
- Internal use:	Pass	EN 14411:2016

Note: (1) where required by regulations

**10.Declaration:** The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: Ali ABACI / General Manager Kütahya/TURKEY- 05.10.2018







## DECLARATION OF PERFORMANCE (According to Regulation EU 305/2011, Annex V)

No: 004DOP-NG

- 1. Identification code of the product type: Dry Pressed Ceramic Tiles With Low Water Absorption, Grup Bla  $E_b \le \%0,5$  Annex G, (GL/UGL)
- 2. Type batch or serial number or any other element allowing identification of the construction product: Identification code of the product type, barcode number, ship date
- 3. Intended use or uses of the construction product,in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: Internal or external floor or wall coverings.
- 4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

NG Kütahya Seramik Porselen Turizm A.Ş. NG Kütahya Seramik Granit Fabrikası Şubesi Trade Mark: NG KÜTAHYA SERAMİK İnköy Mahallesi. 2.Osb 10 Ada 1-2 Parsel Merkez-Kütahya/TURKEY

- 5. Name and contact address of the authorized representative: Not relevant.
- 6. System or system of assesment and verification of constancy of performance of the construction product: System 4
- 7. Declaration of performances concerning a construction product covered by a harmonised Standard: NG Kütahya Seramik performed factory production control under system 4 and issued the certificate of conformity.
- 8. Declaration of performances concerning a construction product for which a European Technical Assesment has been issued: Not relevant.

9. Declared performances:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	A1 <sub>FL</sub> /A1	EN 14411:2016
Breaking strength	Thickness ≥7,5mm >1300 N Thickness <7,5mm >700 N	EN 14411:2016
Slipperiness (1)	Refer to the technical documentation or catalog	EN 14411:2016
Release of dangerous substance, for		
- Cadmium	NPD	EN 14411:2016
- Lead	NPD	EN 14411:2016
Resistance to thermal shock	Pass	EN 14411:2016
Tactility	NPD	EN 14411:2016
Bond strength/adhesion, for:		
- Cementitious adhesives, Type C2	≥ 1,0 N/mm <sup>2</sup>	EN 14411:2016
- Reaction resin adhesives	NPD	EN 14411:2016
- Dispersion adhesives	NPD	EN 14411:2016
Durability for:		
- Internal use:	Pass	EN 14411:2016
- External use: freeze-thaw resistance	Pass	EN 14411:2016

Note: (1) where required by regulations

**10.Declaration:** The performance of the product identified in point 1 and 2 is conformity with the declared performances in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: Ali ABACI / General Manager Kütahya/TURKEY- 05.10.2018

